

SM4600

SANY Electric Terminal Tractor



▶ 1

High torque direct drive system

High efficiency range 10-30km/h;
No gearbox, high transmission efficiency;
Simple structure, simple maintenance;
High braking energy feedback efficiency.

▶ 2

Offset cab

Four sides of glass, wider vision, safe driving;
Air suspension seat + cab air suspension, good comfort;
Side stairs, more convenient to get on and off

▶ 3

Heavy-duty chassis

4×2 heavy load chassis, maximum traction mass 75t;
Box welded girder (14mm), vehicle 3D design and CAE analysis,
high reliability;
30t wheel side two-stage deceleration drive axle, adapt to dock
conditions;
The turning radius is smaller than 7.5m.

▶ 4

Data interconnection

Remote monitoring of vehicle operation data;
Vehicle operation report can be exported;
Fault diagnosis and charging scheduling facilitate vehicle
management and improve operational efficiency.

► Product Parameters

Technical Parameter		
ITEM	UNIT	SM4600
Model/driving type	-	4×2
Overall dimensions	mm	5805×2550×3200
Wheelbase	mm	3400
Endurance	km	≥120
Self weight	t	10
Max. Traction capacity	t	75
Max. Gradeability	%	≥6
Max. Speed	km/h	40
Min. Turning radius	m	7.5
0~30km/h accelerate time	s	≤20

Configuration Parameter			
CONFIGURATION		UNIT	SM4600
Traction battery	Type	-	Charging
	Capacity	kWh	281.9
E-motor	Power	kW	120/240
	Torque	N·m	1200/2800
Charging time		-	Fast charge 60 min
Front axle/rear axle		t	13/34
The fifth wheel	Structure	-	Unfixed
	Heights	mm	1180-1530
Tire		-	12R22.5-18PR
Suspension System		-	SM4600 Fixed SM4601 Air suspension

► Working Picture



MONTREAL (Head office)
100A, Hymus Blvd.
Pointe-Claire (Québec) H9R 1E4

Phone: 514 694-4223
Toll free: 1 866 421-4223

info@elevex.ca



QUEBEC
1279, Paul-Émile Giroux St. Suite
200 Québec (Québec) G1C 0K9

SAGUENAY
2305, Alexis-Le-Trotteur
St. Jonquière (Québec) G7X 9H8



elevex.ca