

ELECTRIC LIFTING PLATFORM

Compact hydraulic design with all safety components complying to EN1570,

High pressure cylinder with dual safety function.

Hard chrome plated piston rods.

Lift and lower by easily push buttons to reach the ergonomically correct working height.

With emergency switch off and a 3m long control cable.

Multiple uses such as: lifting and lowering materials, level compensation when fitting machines, installations in conveyor system etc.



Electric Lifting Platform						
Model	ELF22-24X48	ELF22-48X48	ELF33-36X48	ELF44-48X48	ELF55-32X56	ELF55-48X72
Capacity (lbs.)	2,200	2,200	3,300	4,400	5,500	5,500
Lowered Height (in.)	7.87	7.87	7.87	7.87	9.84	9.84
Raised Height (in.)	39	39	39	39	47	47
Platform Size (WxL) (in)	24 x 48	48 x 48	36 x 48	48 x 48	32 x 56	48 x 72
Net Weight (lbs.)	551	750	705	838	882	1543
Lifting Time (sec.)	20	20	25	50	60	60
Lifting Speed (in./sec.)	1.54	1.54	1.22	0.63	0.63	0.63
Lowering Speed (in/sec)	2.52	2.52	2.52	1.38	0.79	0.79
Motor (kw)	0.75	0.75	0.75	0.75	1.5	1.5
Optional Voltage	115V,60HZ, single-phase / 230V,50HZ,single-phase / 380V,50HZ, 3-phase			230V,50HZ,single-phase / 380V,50HZ, 3-phase		380V,50HZ, 3-phase

Low Profile Electric Lifting Platform				U-shape	
Model	HTF-G11	HTF-G22	HTF-G44	Model	HTF-U22
Capacity (lbs.)	1,100	2,200	4,400	Capacity (lbs.)	2,200
Lowered Height (in.)	3.35	3.23	3.94	Lowered Height (in.)	3.15
Raised Height (in.)	29.92	29.92	39.37	Raised Height (in.)	29.92
Platform Size (LxW) (in)	40 x 24	57 x 45	61.5 x 45	Platform Size (LxW) (in)	57 x 45
Net Weight (lbs.)	212	550	827	Net Weight (lbs.)	518
Lifting Time (sec.)	10	18	55	Lifting Time (sec.)	10
Lifting Speed (in./sec.)	2.95	1.65	0.63	Lifting Speed (in./sec.)	1.65
Lowering Speed (in./sec.)	1.34	1.90	0.90	Lowering Speed (in/sec)	1.9
Motor (kw)	0.75	0.75	0.75	Motor (kw)	0.75
Optional Voltage	115V,60HZ, single-phase / 230V,50HZ, single-phase / 380V,50HZ, 3-phase	230V,50HZ, single-phase / 380V,50HZ, 3-phase	230V,60HZ, 3-phase / 230V,50HZ, single-phase / 380V,50HZ, 3-phase	Optional Voltage	230V,50HZ, single-phase / 380V,50HZ, 3-phase

LOW PROFILE ELECTRIC LIFTING PLATFORM

Compact hydraulic design with all safety components complying to En1570,
High pressure cylinder with dual safety function.

- Hard chrome plated piston rods.
- Lift and lower by easily push buttons to reach the ergonomically correct working height.
- With emergency switch off and a 3m long control cable.
- German steel for sturdy frame & overall durable construction.
- Multiple uses such as: lifting and lowering materials, level compensation when fitting machines, installations in conveyor system etc.



U-SHAPE ELECTRIC LIFTING PLATFORM

This 'U' shaped lift platform is ideal for lifting pallets or cages to a safe working height
and suited for use as a feeding table on an assembly line.

- Supplied with remote power system and control unit with UP, DOWN and EMERGENCY STOP controls.
- The 'U' shape allows a pallet truck to position the pallet/cage onto the lift platform.
- Overload by-pass valve protects operator and pump.



MONTREAL (Head office)
19151 A, Cruickshank Avenue
Baie-D'Urfé (Québec) H9X 3N9
Phone: 418 694-4223
Toll free: 1 866 421-4223
info@elevex.ca
elevex.ca

QUEBEC
1279, Paul-Émile Giroux St. Suite 200
Québec (Québec) G1C 0K9

SAGUENAY
2305, Alexis-Le-Trotteur St.
Jonquière (Québec) G7X 9H8

